



sachtler

ideas in motion

▶ 75 mm

▶ (H)DV

new!

FSB 8 Tech Specs

fluid heads
tripods
pedestals
lighting
camera stabilizing systems



works with
SOOM

▶ Quicklink: www.sachtler.com/en/fsb



sachtler

ideas in motion


▶ 75 mm ▶ (H)DV

FSB 8 / 8 T


Sachtler's strongest 75 mm solution

- Payload range: 1–9 kg / 2–20 lb
- Counterbalance: 10 steps
- 5 horizontal and 5 vertical grades of drag, +0
- Tilt range: +90° to -75° (FSB 8)
+90° to -70° (FSB 8 T)
- For tripods with 75 mm bowls, integrated flat base fitting

MEASUREMENTS IN MM (FSB 8)



MEASUREMENTS IN MM (FSB 8 T)



half ball with screw (integrated flat base)

new!

CODE

FSB 8:

▶ 0707

FSB 8 T:

▶ 0705

SYSTEMS

FSB 8:

SOOM FSB 8

FSB 8 SL MCF

FSB 8 / 2 MD

FSB 8 MD

FSB 8 / 2 D

FSB 8

FSB 8 T:

FSB 8 T SL MCF

FSB 8 T / 2 MD

FSB 8 T MD

FSB 8 T / 2 D

FSB 8 T

BATTERY SYSTEMS FSB 8:

FSB 8 SL MCF PowerSet

FSB 8 / 2 MD PowerSet

FSB 8 MD PowerSet

FSB 8 / 2 D PowerSet

FSB 8 PowerSet

PAYLOAD TABLE


C.O.G.*	min. kg/lb	max. kg/lb
75/3	1.2/2.7	12.2/27.2
100/4	1.0/2.3	10.5/23.1
125/5	0.9/2.0	9.1/20.1
150/6	0.8/1.8	8.0/17.7

*Center of gravity height (mm/in)

PAYLOAD DIAGRAM



DAMPING





FSB 8



FSB 8 T

ACCESSORIES



▶ Quicklink: www.sachtler.com/en/fsb