



SP3 | Basic specification

Specifications	25mm	32mm	50mm	75mm	100mm
T-Stop range	T2.4 - T16				
Angular rotation of iris scale	78°	78°	78°	78°	78°
Min. marked object distance	250 mm	350 mm	500 mm	800 mm	800 mm
	10 in	13 in	20 in	3 ft	3 ft
Close focus from lens front	139 mm	223 mm	394 mm	689 mm	663 mm
	5.5 in	8.8 in	15.5 in	27.1 in	26.1 in
Angular rotation to MOD endstop	160°	160°	160°	160°	160°
Length from front of lens to lens mount (E - Mount)	98 mm	94 mm	94 mm	98 mm	124 mm
	3.85 in	3.7 in	3.7 in	3.85 in	4.88 in
Max. front diameter	64 mm	64 mm	64 mm	64 mm	82 mm
	2.52 in	2.52 in	2.52 in	2.52 in	3.22 in
Max. diagonal angle of view for FF format	81°	69°	47°	32°	25°
Max. diagonal angle of view for S35 format	62°	50°	34°	22°	17°
Total weight (with lens mount)	575 g	520 g	500 g	520 g	690 g
	1.27 lbs	1.15 lbs	1.10 lbs	1.15 lbs	1.52 lbs
Screw-in filter	M58 x 0.75	M58 x 0.75	M58 x 0.75	M58 x 0.75	M77 x 0.75

Maximum format cover	Full Frame, optimised for coverage of 43.3mm
Focus scales	Dual Focus Non-Linear scales - Imperial and Metric, scales marked from infinity to MOD
Focus drive gear	83 teeth 0.8 Metric Module
Iris scales	Non-Linear scale, whole and third stops marked
Iris drive gear	83 teeth 0.8 Metric Module
Mount	E, RF*, L, M** (L-mount and M-mount sold separately)

*RF-mount will be available soon after launch. Purchasers will be able redeem a set free of charge by following the instructions in the packaging.

**M-mount available early 2024.

Version: 083023

Cooke Optics Limited | Cooke Close, Thurmaston, Leicester, LE4 8PT | T +44 (0)116 264 0700 | E lenses@cookeoptics.com | cookeoptics.com