Halogen non-reflector

7158XHP 150W G6.35 24V 1CT

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

Product data

• General Characteristics

Philips Code	7158XHP
ANSI Code	FCS
LIF Code	A1/216
Cap-Base	G6.35
Bulb Material	Quartz-UV Open
Filament Shape	Flat
Operating Position	s90
Main Application	Projection
Life to 50% failures	40 hr

• Light Technical Characteristics

Color Rendering Index	100 Ra8
Color Temperature Technical	3400 K
Luminous Flux Lamp	6000 Lm

• Electrical Characteristics

Lamp Wattage	150 W
Voltage	24 V

• Luminaire Design Requirements

Pinch Temperature	400 (max) C
Bulb Temperature	900 (max) C

### • Product Dimensions

Diameter D	13.5 (max) mm
Light Center Length L	32.75 (min), 33 (nom), 33.25 (max) mm
Pin Diameter P	0.95 (min), 1 (nom), 1.05 (max) mm
Filament Dimensions (WxH) [mm]	7.4x3.5

• Product Data

|	
Order code	924031720503
Full product code	924031720503
Full product name	7158XHP 150W G6.35 24V 1CT
Order product name	7158XHP 150W G6.35 24V 1CT/ 10X10F
Pieces per pack	1
Packing configuration	10X10F
Packs per outerbox	100
Bar code on pack - EAN1	8711500410207
Bar code on inter-mediate packing - EAN2	8711500420381
Bar code on outerbox - EAN3	8711500423221
Logistic code(s) - 12NC	924031720503
Net weight per piece	0.004 kg

PHILIPS

Dimensional drawing

7158XHP 150W G6.35 24V 1CT

Product	C (Norm)	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	P (Min)	P (Norm)	P (Max)
7158XHP 150W G6.35 24V	-	-	13.5	32.75	33	33.25	0.95	1	1.05

max.25

6.35

G6.35

www.philips.com/lighting

2014, October 31
data subject to change