I maxisuitch The Newest (AND LARGEST) FAMILY MEMBER

MAXI SWITCH

Built from two separate panels and joined together by a smart hinge, the bi-folding MAXI Switch is a mechanical marvel!

Reference code	MAXI-HL-SW
Light Panel Dimensions	1250 x 754 x 23 mm 48 x 30 x 0.75 "
Max Power Consumption	520 Watts
Light Panel Voltage Input	24VDC / 22Amps
Weight	12.5 kg 27 lb
Dimming	Flicker Free at Any FPS – 0 to 100% (2 speeds)
AC Power	100 to 240 VAC
Battery Connection	Optional 3-pin XLR / Chogori Cable
Battery DC input Voltage Range:	24 to 30 VDC

Type of LEDs	SMD2835
Number of LEDs	8640
Colour Temperature Range	3000 to 5600°k
CRI	94% @3200°k – 96% @5600°k
TLCI-II	91% @3200°k – 94% @5600°k
Diffusion	Frosted Acrylic Diffuser
Standard Mounting	Value
Standard Mounting	Yoke
Light Panel DC Connector	Neutrik SpeakOn
Light Panel DC Connector	Neutrik SpeakOn
Light Panel DC Connector Housing Material	Neutrik SpeakOn Black Anodised Aluminium and Stainless Steel Screws
Light Panel DC Connector Housing Material Silent Cooling	Neutrik SpeakOn Black Anodised Aluminium and Stainless Steel Screws Passive Cooling Technology – No Fins, No Fans



PHOTOMETRICS

METRES	З	5	7
@3200°K Lux	1730	654	370
@5600°K Lux	1880	700	399
FEET	9.8	16.4	22.9
@3200°K FC	161	61	34
@5600°K FC	175	65	37

l maxiswitch

POWER - MAXI DRIVER

Advanced DC driver with DMX wired and wireless function (Lumen Radio RX/TX chip) and WiFi / Lan input. Coloured control screen and Chogori input connector . Neutrik SpeakOn output connector. Mounts directly on to the back of the MAXI Panel and PSU.

Reference code	MAXI-CT-SW
Size	30 x 16.5 x 6 cm 11.8 x 6.3 x 2.4 "
Weight	2.420 kg 5.3 lb
Dimming curve	Flicker Free at Any FPS – 0 to 100% (2 speeds)
Input / Output Voltage	24 to 28 VDC / 24VDC Constant Current
Housing Material	Black Anodised Aluminium and Stainless Steel Screws
Certifications	CE, CSA, RoHS



THE MAXI DRIVER CAN BE BATTERY POWERED WITH 24-28 VDC INPUT (20 AMPS)



POWER - MAXI AC POWER SUPPLY

External and universal power supply. Neutrik PowerCon input connector (Daisychain possible) with optional cable) and Chogori output connector.

Reference code	MAXI-PSU-SW
Size	30 x 19 x 6 cm 11.8 x 7.5 x 2.4 ''
Weight	5,340 kg 11.8 lb
Max power draw	520W
Input / Output Voltage	24 to 28 VDC / 24VDC Constant Current
Housing Material	Black Anodised Aluminium and Stainless Steel Screws
Certifications	CE, CSA, RoHS

DMGLUMIERE.COM