

# SOFTUBE

200, 400, 800 and 1600

**K 5600**<sup>®</sup>  
LIGHTING



## INFORMATION

The Softtube is an accessory to the Joker light. It transforms a normally spotty narrow beam into a soft and even linear source. These characteristics make the Softtube the perfect corner light: ideal for window reinforcement, large vehicle interiors and wherever a compact long soft source is needed. Easy and quick set up saves the lighting crew valuable production time. HMI quality, low heat, high output.

The Softtube is based on the fiber light guides principle where a beam is trapped inside a volume by multiple reflections and goes out through a selective path. The emitting source must be a highly concentrated light beam. The unit consists of three parts: the attachment ring, the translucent Joker Gel and the mirror cap.

## SPECIFICATIONS

### DIMENSIONS SOFTUBE 1600:

- SIZE: 69" X 9.5"
- WEIGHT: 7.5 LBS

### PHOTOMETRICS SOFTUBE 1600:

Distance	Fc.
3'	950
6'	275
10'	99

### DIMENSIONS SOFTUBE 800:

- SIZE: 46.5" X 7.69"
- WEIGHT: 4.6 LBS

### PHOTOMETRICS SOFTUBE 800:

Distance	Fc.
3'	580
6'	145
10'	52

### DIMENSIONS SOFTUBE 400:

- SIZE: 45" X 6"
- WEIGHT: 3 LBS

### PHOTOMETRICS SOFTUBE 400:

Distance	Fc.
3'	330
6'	83
10'	30

### DIMENSIONS SOFTUBE 200:

- SIZE: 33" X 46"

### PHOTOMETRICS SOFTUBE 200:

Distance	Fc.
3'	127
6'	32
10'	11